

PRODUCT DATA SHEET

EEBD EMERGENCY EVACUATION BREATHING DEVICE



ESCAPE-15

- Full-face hood universal size, suitable for every face shape
- Durable, elastic and non-irritant neoprene neck seal
- 15 min. steady air-flow with sufficient air-delivery rate
- EU standard valve with G 5/8" charging thread
- Flame resistance
- Activated with a single move



- Easy visual access on the pressure gauge
- Durable & reliable construction with low maintenance
- Silver colour to reflect heat and be highly visible (70321)
- Easy to refill cylinder (no adaptor required)
- Available option with carbon composite cylinder upon request (703211)
- Shelf life is 10 years, or 15 years (for carbon composite cylinder), from the date of the cylinder's manufacture
- An alarm whistle sounds before the air supply is exhausted (available upon request)



Technical Specifications

Code	70321	703211
Cylinder Volume (L)	3	
Cylinder Material	Steel	Carbon
		Composite
Approvals	SOLAS /	SOLAS /
	MED-MER	MED
Working Pressure (bar)	200	
Working Temp. Range (°C)	-10°C to 65	
Length (cm)	50	53
Height (cm)	22	21
Width (cm)	13	11
Weight (g)	6.150	4.500
Volume (cm ³)	14.300	12.200

10.25.7.5

* The product is tested per the following Regulations and Standards:
• SOLAS 74 as amended • Regulation II-2/13 • FSS Code 3 • IMO MSC/Circ. 849
- Tested according to ISO 23269-1:2008 and EN 1146:2005



Worldwide spare parts availability through our network.



www.lalizas.com



Global Service & Supply Network





- Global service network through owned locations & third-party service providers
- Global supply of LSA, FFE and spare parts
- Certified quality standards by major classification societies
- Robust warranty supported directly by the manufacturer
- Streamlined after-sales support via our ticketing system

Safety is not just a product, it is an ongoing process!

www.lalizas.com