

## PRODUCT DATA SHEET

### LALIZAS Antipiros Fireman's Jacket & Trousers, SOLAS/MED

- Made of three different layers\* for excellent thermal protection and endurance.
- Navy blue colour with reflective trim.
- Flame retardant reflective tapes are arranged • at the circumference of the jacket, hem, sleeve cuff and bottom of trousers to ensure visibility and work safety of firefighter.
- Extra layers for abrasion resistance in neck, elbows and knees.
- Stand-up collar, with overlapping closure.
- Front flame retardant zipper lockable with • velcro tape.
- DRD lifesaving drag belt included.
- Cuff with rib thumb hole.
- Velcro strap at waist and waistband adjustment loop on trousers.
- Detachable and adjustable suspender with velcro hook and loop fastener for excellent fit and comfort.
- · All pockets are specially designed in accordance with shape features and usage habit of firefighter. External pockets can extend over 10mm and can be fastened shut. Radio pockets included.
- Drain hole in the bottom of the pockets to • reduce damage to equipment caused by water during firefighter duties.

#### \*Layers:

- 1st Layer, Outer fabric:
- Ripstop Nomex Kevlar Material, 210gsm 2nd Layer, Moisture barrier fabric:
- Aramid and PTFE Material, 160gsm 3rd Layer, Thermal lining fabric:
- Nomex and FR Viscose,180gsm
- X2 Highest level of heat protection, includes combined protection against contact, flame
- X2 Highest level of heat protection, includes combined protection against radiation heat transfer
- Y2 Highest level of resistance to water penetration
- Z2 Highest level of water vapor resistance



**Specified Testing Standards:** EN ISO 13688:2013, EN 469:2020, XL SOLAS 74 Reg. II-2/10, SOLAS 74 Reg. X/3, 195 IMO Res. MSC.98(73) - (FSS Code) 3, IMO Res. MSC.36(63) - (1994 HSC Code) 7, 144 IMO Res. MSC.97(73) - (2000 HSC Code) 7 Tolerance Range (cm) ±1.5 ±2.0

75182 75183

L

185

136



Rinse off chemical spillages immediately with water. Re-proof after every 5th wash.



## www.lalizas.com

Code

Size

Height (cm)

Chest Girth (cm)

#### LEVEL 2 according to new testing standard EN469:2020

Provides the highest protection levels in thermal performance (contact heat – heat transfer), water penetration and water vapor resistance.





# **Global Service & Supply Network**





- Global service network through owned locations & third-party service providers
- Global supply of LSA, FFE and spare parts
- Certified quality standards by major classification societies
- Robust warranty supported directly by the manufacturer
- Streamlined after-sales support via our ticketing system

# Safety is not just a product, it is an ongoing process!

www.lalizas.com