

Lifelink Rescue Sling

The LifeLink Rescue sling system is designed to be permanently mounted to the rail in it's own soft, easy to clean, PVC bag. It is used for MOB retrieval and meets the ISAF regulation.

Easily accessible to be used when in need, it contains 36m of floating line, attached to a sturdy buoyant PVC rescue-sling and a personal retaining clip for added safety.

Deployment is achieved simply by removing the Rescue Sling and throwing it astern, since you have already attached it firmly (when installed) in the rails. Once in the water, the boat should circle the casualty, allowing the Rescue-sling to be towed to their aid.

Rescue is completed when the casualty is safely clipped into the LifeLink, winched to the boat and hauled on board.

Available in white (code 73670) and yellow (code 20440) color.

Contents:

Rail mounted PVC stowage bag 36m floating line Soft PVC Life Link with webbing strap

Features:

Breaking strain of line > 200 kg. Breaking strain of flotation belt > 700 kg.

Meets ISAF regulation





How to attach on the rails

















How to retie the knot to the Lifelink



1. Put the line through both D-rings and hold steadily the short end. Make a loop with the long end and pass through it the short rope.



2. Then pass the same end under and around the long part and through the loop again.



3. To fasten pull together from points A and B

Procedures for repacking the Lifelink



To repack the line:
Leave 50cm of line outside the bag.
Hold with your right hand



2. Measure another 50cm and fold the rope in two to create a "U" shape. Place the folded rope in the inside pocket of the bag.



3. a) Holding the line going to the Life-Link with the right hand, start gathering it creating a zig-zag. The width of the zig-zag should be approx. 20cm. b) Continue in the same way, until enough line is collected in your hand



4. Place this in the inside pocket gently.
Repeat step 3 until all the line is gathered in the pocket in an orderly fashion.


ATTENTION:

End of line must always be attached to boat.

Care should be taken when re-packing the retrieval line to ensure successful deployment



1. Deploy M.O.B. system astern circle casualty until contact is made.



2. Confirm casualty is secured in M.O.B. Before rescue is attempted.



3. Winch casualty slowly to the boat.



4. Haul casualty on board.